



FOOD GRADE AIR TOOL LUBE (FG-ATL)

ATL-(FG-ATL) Food Grade Air Tool Lube is a superior food grade synthetic air tool lubricant. It is made from advance technology synthetic food grade base stocks and FDA H-1 approved additives to provide maximum lubrication, cleaning, and protection for modern air tools where incidental food contact is possible.

ATL-(FG-ATL) - Food Grade Air Tool Lube removes deposits and cleans stuck air tools. It provides outstanding service in even the most severe operating conditions providing extended equipment life.

ATL-(FG-ATL) - Food Grade Air Tool Lube meets FDA H-1 (21 CFR 178.3570), and is recommended for applications where incidental food contact is possible.

ATL-(FG-ATL) - Food Grade Air Tool Lube is an excellent choice for in-line lubricant for air delivery systems.

Typical Properties

Lubricant Designation	FG-ATL
Viscosity Index	127
Viscosity cSt @ 40 C	22.1
Viscosity cSt @ 100 C	4.6
Viscosity SUS @ 100 F	106.3
Viscosity SUS @ 212 F	41.4
Flash Point F	315
Auto-Ignition Point F	655
Pour Point F	-20
Oxidation Stability	10,000
Color<.5	
Copper Corrosion, 24 Hr	1a
Rust Test	PASS
Demulsibility, 130 F, 30 min	40/40/0

Advanced Technology Lubricants Inc.
4430 Eastport Parkway Suite 3
Port Orange, FL 32128
Ph. 386.322.1666 Fx. 386.322.0509
ATLubricants.com